- Clear plastic cover for fast visual confirmation of fuse amp rating.
- Easy identification of blown fuses when LED indicating Auto fuses are installed.

Part Number	No. Poles	Max Amps Per Block	Included Terminals
00540K	4 Pole	80A	8 x 07501
00560K	6 Pole	100A	12 x 07501
00580K*	8 Pole	135A	16 x 07501

Voltage: 32V

Input Terminal Rating: 20A max. per circuit.

Body: Black PA66 GF30

Cover: Transparent cover. *00580K cover features a gasket.

Terminals: Axial connections, 6.35mm (1/4") Quick Connect terminals.

Kit Contents: Cover, base & QC terminals.

Mounting: M5 screw (00540K & 00560K), M5 threaded insert (00580K).

Pack Size: 1, 10, 100, 500


Options: Blocks and terminals can be ordered separately, minimums apply. **Notes:** Each fuse branch is independently powered. Fuses are not included.

Approvals: RoHS



07501 1/4"Quick Connect Male Terminals

Mounting Diagram




00540K 4 Way Axial Kit





53.2

Mounting Diagram




00560K 6 Way Axial Kit



73.2


Mounting Diagram



00580K 8 Way Axial Kit



Dimensions in MM





Email: info@prolecproducts.com Web: www.prolecproducts.com