M205 / 3AG PANEL MOUNT FUSE HOLDERS


EATON Bussmann

Part Number	FuseType	Knob Type	Terminal Type / Angle	Rating (UL)
HTB-24M-R	M205	Fingergrip	Q/C 4.8mm or Solder, Right	16A @ 250V
HTB-34M-R	M205	Screwdriver	Q/C 4.8mm or Solder, Right	16A @ 250V
HTB-22I-R	3AG	Fingergrip	Q/C 4.8mm or Solder, Straight	20A @ 250V
HTB-34I-R	3AG	Screwdriver	Q/C 4.8mm or Solder, Right	20A @ 250V
HTB-26I-R	3AG	Fingergrip	Q/C 6.35mm, Straight	20A @ 250V


IPxx Optional

Voltage: 250V
Terminals: Tin plated brass.
Mounting Standard: Low profile, rear hex nut.
Mounting Option: High profile also available, please contact sales.
Ambient Temperature: -55°C to +85°C.
Body: High temperature, flame retardant thermoplastic UL 94VO.
Accessories: Includes plastic nut and spacer.
Options: Finger-grip type holders may be ordered with 'splash proof' knob (by adding 'SP' to the part number eg.HTB-22ISP). Spare nuts also available in plastic or metal.
Pack Size: 10, 100
Notes: Fuse is not included.
Approvals: RoHS

Finger Grip Knob



Mounting Hole Double D



Max. Panel Thickness: 7.62mm

Terminal Options



Straight 4.8mm (3/16") Quick Connect (Q/C) or Solder



Right 4.8mm (3/16") Quick Connect (Q/C) or Solder





Straight 6.35mm (1/4") Quick Connect (Q/C)



Right 6.35mm (1/4") Quick Connect (Q/C)

Screwdriver Knob





Dimensions in MM

RELATED PRODUCTS:



M205 Fuses (p14-15)



3AG Fuses (p16-17)

3AG FUSE HIGH PROFILE PANEL MOUNT HOLDER

EATON Bussmann


Part Number
HKP




Finger Grip Knob


Rating: 30A
Voltage: 250V
Pack Size (bag): 10, 100
Knob: Bayonet type knob
Notes: Vibration resistant
Notes: Fuse is not included.
Approvals: RoHS Optional

Mounting Hole Single D





Dimensions in MM



RELATED PRODUCTS:

Fuses: 3AG / 3AB (p16-17)

